

# T7PRC Terminal

Wireless Terminals from Hypercom

*Hypercom's new portable, wireless, battery-powered T7PRC terminal offers versatility and convenience.*

## Product Highlights:

- ✓ Uses cost-effective Cellular Digital Packet Data (CDPD) technology.
- ✓ Works with all Hypercom® standard T7P/T7E applications.
- ✓ Eliminates the need for a dedicated phone line.
- ✓ Integrated printer provides complete POS functionality in a small footprint.

Hypercom's new T7PRC cellular terminal offers the features and benefits of the popular T7P with the added convenience of wireless operation capability.

The T7PRC eliminates the expense of a dedicated phone line in any retail environment.

Optional external antenna provides improved operation in areas with limited coverage.

Aimed at temporary location merchants such as special events and kiosks, as well as mobile services such as delivery vans and taxis, the T7PRC offers a quality wireless POS solution.



T7PRC shown in remote situation



*The Future of Transaction Technology*

**1-800-578-2436**

2851 W. Kathleen Road, Phoenix, AZ 85053  
Tel: (602) 504-5000 • Fax: (602) 504-4578

# T7PRC

## Specifications

<b>Protocol</b>	SDLC (Synchronous) and Asynchronous (VISA 1 & 2)
<b>Display</b>	2 x 20 back-lit LCD
<b>Keyboard</b>	35 keys
<b>Memory</b>	
<b>EPROM</b>	32k
<b>RAM</b>	256k
<b>Optional</b>	1 Mb
<b>Card Reader</b>	Tracks 1 & 2
<b>Communications</b>	LAN, RS485, 2 or 4 wire
<b>Power</b>	+24 Vdc, 200 mA
<b>Mobile Option</b>	+12 Vdc-24 Vdc conversion with Hypercom FPW1
<b>Battery Option</b>	80 transactions between recharges
<b>Auxiliary Ports</b>	PIN Pad RS422/RS485
<b>Dimensions</b>	6 1/4" W x 11 1/2" D x 5 1/2" H* *(with full 3" diameter roll of paper)
<b>Weight</b>	4.3 lbs. with paper
<b>Memory/Clock Back-up</b>	Lithium Battery (5 years)
<b>Operating Temperature</b>	0°C to +45°C
<b>Relative Humidity</b>	15-85 percent, noncondensing
<b>ESD Resistance</b>	12,000 volts
<b>Printer</b>	Integrated roll printer @ 1.7 lines/second, 40 columns, 2-ply no-carbon paper, 2 1/4" wide by 100' (3" diameter roll), 5x7 font 1200 or 2400bps
<b>Modem</b>	
<b>Reliability</b>	
<b>Key Life</b>	350,000 operations
<b>Card Reader</b>	900,000 reads
<b>Printer</b>	1,500,000 lines MCBF
<b>Antenna</b>	Magnetic mount TNC with 3 db gain on 4 ft. cable
<b>Options</b>	Graphics Display (64 x 128) QWERTY Keyboard Memory upgrades to 1 Mb Rechargeable battery



### Corporate Office

2851 West Kathleen Rd. • Phoenix, Arizona 85053  
Tel: (602) 504-5000 • Fax: (602) 504-4578  
1-800-578-2436

### World Wide Web Site

<http://www.hypercom.com>

## CDPD Cellular General Information

<b>Frequency Coverage</b>	
<b>Transmit Rating</b>	824-849 MHz
<b>Receive Rating</b>	869-894 MHz
<b>Channel Spacing Rate</b>	30 KHz
<b>Protocol</b>	TCP/IP
<b>RF Power Output</b>	3 watts maximum
<b>Airlink Data Rate</b>	19,200 bits per second
<b>Antenna</b>	Integrated or external
<b>Software</b>	
<b>Software Loading</b>	Telco Line
<b>Terminal Initialization</b>	Cellular

### International Offices

Hypercom Latin America  
Miami, Florida  
Tel: (305) 477-0315  
Fax: (305) 477-4172

Hypercom Asia Pacific  
Kowloon Bay, Hong Kong  
Tel: 852-2561-6800  
Fax: 852-2561-5890

Hypercom EMEA  
Surrey, England  
Tel: 44-1483-718600  
Fax: 44-1483-718601

### Regional Sales Offices

Atlanta, GA  
Tel: (770) 641-7117  
Fax: (770) 645-4490

Chicago, IL  
Tel: (708) 301-6820  
Fax: (708) 301-6841

Los Angeles, CA  
Tel: (310) 455-0708  
Fax: (310) 455-2959

New York, NY  
Tel: (516) 676-5779  
Fax: (516) 676-5806